



Air cooled screw
chiller, high
efficiency,
reduced sound

EWAD-D-XR

R-134a



Screw compressor

- › 2 truly independent refrigerant circuits
- › Stepless single-screw compressor
- › Optimised for use with R-134a

- › Large operation range (ambient temperature down to -18°C)


EWAD-D-XR



Cooling only				EWAD-D-XR	240	270	300	320	350	370	390	460	510	560	600
Cooling capacity	Nom.		KW	242	271	294	321	343	369	393	453	510	559	598	
Power input	Cooling	Nom.	KW	81.6	88.0	96.3	107	117	121	129	154	169	185	200	
Capacity control	Method			Stepless											
	Minimum capacity		%	12.5											
EER				2.96	3.07	3.06	3.00	2.94	3.06	3.05	2.95	3.01	3.02	2.99	
ESEER				3.52	3.59	3.58	3.71	3.60	3.89	3.71	3.77	3.99	3.81		
IPLV				4.03	4.11	4.12	4.17	4.13	4.28	4.25	4.36	4.79	4.78	4.47	
Dimensions	Unit	Height	mm	2,355								2,223			
		Width	mm	2,234											
		Depth	mm	3,138	4,040						4,940				
Weight	Unit		kg	3,005	3,385		3,335		3,340		3,610	4,770	4,785		
	Operation weight		kg	3,100	3,500						3,880	5,040			
Water heat exchanger	Type			Single pass shell & tube											
	Water flow rate	Cooling	Nom.	l/s	11.6	13.0	14.1	15.4	16.4	17.7	18.8	21.7	24.4	26.8	28.6
	Water pressure drop	Cooling	Nom.	kPa	47	44	48	45	49	56		45	60	54	36
	Water volume			l	95	115		165		160		270		255	
Air heat exchanger	Type			High efficiency fin and tube type with integral subcooler											
Compressor	Type			Single screw compressor								Asymmetric single screw compressor			
	Quantity			2											
Fan	Type			Direct propeller											
	Quantity			6	8						10				
	Air flow rate	Nom.	l/s	17,892	24,777	23,856			33,035	32,576	33,493	41,867			
	Speed		rpm	680						705					
Sound power level	Cooling	Nom.	dB(A)	92						93		94			
Sound pressure level	Cooling	Nom.	dB(A)	73						74					
Operation range	Air side	Cooling	Min.-Max.	°CDB -18~48											
	Water side	Cooling	Min.-Max.	°CDB -15~15											
Refrigerant	Type/GWP			R-134a/ 1,430											
	Circuits	Quantity		2											
Refrigerant charge	Per circuit		kg	30.0	31.0	38.0	39.0	40.0	39.0		34.0	45.0	47.0	50.0	
			TCO ₂ Eq	42.9	44.3	54.3	55.8	57.2	55.8		48.6	64.4	67.2	71.5	
Piping connections	Evaporator water inlet/outlet (OD)			4"								6"			
Unit	Starting current	Max	A	222	237		280	289	306		417	473	491		
	Running current	Cooling	Nom.	A	134	144	160	175	188	200	213	256	283	308	330
			Max	A	173	193	210	222	233	257	272	317	351	373	396
Power supply	Phase/Frequency/Voltage		Hz/V	3~/50/400											

Cooling: entering evaporator water temp. 12°C; leaving evaporator water temp. 7°C; ambient air temp. 35°C; full load operation.
 Equipment contains fluorinated greenhouse gases. Actual refrigerant charge depends on the final unit construction, details can be found on the unit labels.

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-427_6 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.