



Air cooled screw
inverter chiller,
standard
efficiency,
standard/reduced
sound

EWAD-TZSS/SR

R-134a



Inverter



Screw compressor

- › Optimised energy efficiency both at full and part load conditions
- › Advanced compressor technology featuring integrated inverter and variable volume ratio (VVR)
- › Compact design for small footprint and minimized installation space

- › Low operating sound levels are achieved by the latest compressor and fan design
- › One or two truly independent refrigerant circuits for outstanding reliability


EWAD-TZSS/SR



Cooling only				EWAD-TZSS/SR																	
				170	205	235	270	320	365	370	415	465	500	540	590	640	710				
Cooling capacity	Nom.	kW		170	205	229	268	317	365	366	412	463	499	536	589	640	710				
Power input	Cooling	kW		62.2	72.5	79.1	96.0	116	133	134	145	164	178	190	217	235	267				
Capacity control	Method	Stepless																			
	Minimum capacity	%		33.3	28.6	33.3	28.6	25.0	22.2	15.4	14.3	16.7	15.4	14.3	13.3	12.5	11.1				
EER					2.73	2.83	2.90	2.79	2.74		2.85	2.83	2.80	2.82	2.72	2.73	2.66				
ESEER					4.48	4.61	4.67	4.64	4.67	4.65	4.61	4.73	4.81	4.82	4.75	4.79	4.75	4.71			
IPLV					5.33	5.44	5.90	5.68	5.67	5.73	5.86		5.83	5.91	5.88	5.95	5.78				
Dimensions	Unit	Height	mm	2,270						2,222											
		Width	mm	1,224						2,258											
		Depth	mm	3,461	4,361		5,261		3,218		4,117		5,015		5,917						
Weight (SS)	Unit	kg		1,898	1,977	2,083	2,478	2,444	2,756	3,906	4,256	4,426	4,481	4,709	4,892	4,969	5,291				
	Operation weight	kg		1,915	2,077	2,183	2,504	2,596	2,806	3,995	4,426	4,590	4,645	4,873	5,162	5,231	5,553				
Weight (SR)	Unit	kg		1,996	2,075	2,181	2,576	2,541	2,854	4,101	4,452	4,621	4,676	4,904	5,087	5,164	5,486				
	Operation weight	kg		2,013	2,174	2,280	2,602	2,693	2,903	4,190	4,622	4,785	4,840	5,068	5,357	5,426	5,748				
Water heat exchanger	Type	Plate heat exchanger																			
	Water volume	l		17	24		26	39	50	89	170	164		270	262						
	Water flow rate	Cooling	Nom.	l/s		8.1	9.8	11.0	12.8	15.1	17.4	17.5	19.7	22.1	23.9	25.6	28.2	30.6	34.0		
Air heat exchanger	Type	High efficiency fin and tube type with integral subcooler																			
	Compressor	Type	Inverter driven single screw compressor																		
Fan	Quantity	1																			
	Type	Direct propeller																			
Sound power level (SS)	Quantity	3		4		5		6		8		10		12							
	Air flow rate	Cooling	Nom.	l/s		12,399	16,532	16,015	20,665	20,019	24,023	33,064	32,030	41,330	40,038	48,046					
	Speed	Cooling	Nom.	rpm		700															
Sound power level (SR)	Cooling	Nom.	dBA		96	97	96	97	98	101	99	100	99	100	101	104					
	Cooling	Nom.	dBA		89				90	92				93		95					
Sound pressure level (SS)	Cooling	Nom.	dBA		77				78	82	80	79	80		81	84					
	Cooling	Nom.	dBA		70	69	70	71	73		72		73		74						
Operation range	Water side	Cooling	Min.~Max.	°CDB		-8~15															
	Air side	Cooling	Min.~Max.	°CDB		-18~47															
Refrigerant	Type / GWP	R-134a / 1,430																			
	Circuits	Quantity	1						2												
Refrigerant charge	Per circuit	kg		29.0	35.0	39.0	46.0	54.0	62.0	31.0	35.0	39.5	42.5	45.5	50.0	54.5	60.5				
	Per circuit	TCO ₂ Eq		41.5	50.1	55.8	65.8	77.2	88.7	44.3	50.1	56.5	60.8	65.1	71.5	77.9	86.5				
Piping connections	Evaporator water inlet/outlet (OD)	88.9mm						114.3mm		139.7mm				168.3mm							
Unit	Maximum starting current	A		3																	
	Nominal running current (RLA)	Cooling	A		106	123	134	161	194	221	226	245	277	299	319	365	392	441			
	Maximum running current	A		121	144	158	187	217	248	262	287	316	342	374	406	434	496				
Power supply	Phase/Frequency/Voltage	Hz/V		3~/50/400																	

(1) Cooling: entering evaporator water temp. 12°C; leaving evaporator water temp. 7°C; ambient air temp. 35°C; full load operation. | Equipment contains fluorinated greenhouse gases. Actual refrigerant charge depends on the final unit construction, details can be found on the unit labels.

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-432_1 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.